



155TS2

DIRECT MOUNT EJECTOR SCRAPER



15.5yd³ HEAPED CAPACITY



108.5" CUTTING WIDTH



250-620 RECOMMENDED HORSEPOWER



With additional capacity over other agricultural earthmovers, the 155 series is the perfect match for operators with horsepower to spare. The 155TS2 was created for customers who asked for added capacity, ease of transport, and increased cutting width. Stay within budget without sacrificing all the bells and whistles. This scraper comes standard with high flotation tires, GPS ready framework, 5 piece blade set, and a ride control hydraulic accumulator.

THE 155TS2 HAS WITHSTOOD THE TEST OF TIME, PERFECTLY FITTING THE NICHE OF SIZE, VERSATILITY AND MANEUVERABILITY.



EQUIPMENT FEATURES

- › High-flow sequence and counter-balance valve manifold system
- › Ball bushing in ejector cylinder
- › Steel bulkhead
- › Laser pad on cross-member
- › Hydraulic hose stand
- › Ejector sidewall rollers
- › Trunnion-block featuring improved Grease retention
- › 16" diameter, 11/16"+ wall front pipe
- › 2.11 gallon Nitrogen over hydraulic accumulator
- › Center stinger blade or optional serrated center blade, left and right corner blades and side router bits
- › 7/8" plow bolts
- › 5.75" Super high capacity spindles and 14-bolt welded hubs
- › Rear Tires (2): 29.5 x 25 - Bias 28-ply
- › Industrial multi-piece split-rim
- › Tilting 31" rack with cutouts for visibility and top loading ease
- › Dual-plated floor
- › Arched front cross-member
- › Specialized large-based flanged wheel nuts
- › Convenient grease zerks in all hubs
- › 1-Year Warranty

SPECIFICATIONS

Heaped Capacity	15.5 yd ³ (11.9 m ³)
Recommended HP	250-620 hp (186-462 kw)
Width of Cut	108.5" (275.6 cm)
Apron Clearance	62" (157.5 cm)
Ejector Cylinder (1)	5" x 60" (127 mm x 1,524 mm)
Apron Cylinder (2)	4" x 13" (102 mm x 330 mm)
Lift Cylinder (2)	5" x 20" (127 mm x 508 mm)
Laser/GPS Bracket	Standard
Tires Std. Rear	(2) 29.5 x 25
Overall Width	120" (304.8 cm)
Overall Length	360" (914.4 cm)
Overall Height	95" (241.3 cm)
Weight Lead Config.	21,308 lb (9,665 kg)
Weight Rear Config.	20,808 lb (9,438 kg)



**DOUBLE CAPACITY
TO 31 CU. YDS. WITH
A TANDEM SETUP**