



CONSTRUCTION LEVELERS

With the largest drag capacity on the market, K-Tec Land Levelers help contractors score a perfect grade on construction haul roads and land leveling projects. Our lineup of construction levelers helps you to keep a smooth haul road which allows for faster cycle times and less structural damage to your equipment. Ranging from 14' to 20' / 4.2m to 6m in width and with the ability to drag between 11 - 16 cubic yards / 8.4 - 12.2 cubic metres, these effective earthmovers save you time and money.



K-TEC CONSTRUCTION LEVELER FEATURES

14-20' WIDTH

**ADAPTABLE
GPS LASER**

**TURNING RADIUS
90°**

**PRECISION DEPTH
LEVEL GAUGE**

SIMPLISTIC TILT

**MECHANICAL
SLOPE METER**

**FOLDABLE HITCH
ROAD TRANSPORT**

SHIPPING

**1 YEAR
STRUCTURAL
6 MONTH
PARTS & LABOR**

CONSTRUCTION LEVELER SPECIFICATIONS

MODEL	BUCKET DIMENSIONS		CAPACITY		CUTTING WIDTH	
	Standard	Metric	Standard	Metric	Standard	Metric
1411 Flex	14' W x 5' 1" H x 4' 7" L	4.26m W x 1.5m H x 1.4m L	11.4 Cubic Yards	8.7 Cubic Metres	14'	4.26m
1613 Flex	16' W x 5' 1" H x 4' 7" L	4.9m W x 1.5m H x 1.4m L	13 Cubic Yards	10 Cubic Metres	16'	4.9m
1814 Flex	18' W x 5' 1" H x 4' 7" L	5.4m W x 1.5m H x 1.4m L	14.6 Cubic Yards	11.1 Cubic Metres	18'	5.5m
2016 Flex	20' W x 5' 1" H x 4' 7" L	6.1m W x 1.5m H x 1.4m L	16.3 Cubic Yards	12.5 Cubic Metres	20'	6.1m

STANDARD FEATURES
Single Simplistic Tilt
Depth Level Gauge
Mechanical Slope Meter
GPS/Laser Adaptability
385/65 R22.5 x 4 Tires

TRANSPORT DIMENSIONS

MODEL	OVERALL WIDTH & LENGTH		SHIPPING WEIGHT		FOLDED DIMENSIONS	
	Standard	Metric	Standard	Metric	Standard	Metric
1411 Flex	14' 3" W x 25' L	4.34m W x 7.62m L	10,135 lbs	10,135 lbs	8' 6" W x 10' 6" H x 22' L	2.59m W x 3.2m H x 6.7m L
1613 Flex	16' 3" W x 25' L	4.95m W x 7.62m L	10,600 lbs	4,808 kgs	8' 6" W x 10' 6" H x 23' L	2.59m W x 3.2m H x 7.0m L
1814 Flex	18' 3" W x 25' L	5.56m W x 7.62m L	11,065 lbs	5,019 kgs	8' 6" W x 10' 6" H x 24' L	2.59m W x 3.2m H x 7.31m L
2016 Flex	20' 3" W x 25' L	6.17m W x 7.62m L	11,530 lbs	5,230 kgs	8' 6" W x 10' 6" H x 25' L	2.59m W x 3.2m H x 7.62m L

OPTIONAL FEATURES
LED Lights
Rear Hitch

HYDRAULIC CONFIGURATIONS
1/2" Tips
3/4" Tips

RECOMMENDED POWER UNITS

Utility Tractor

1411 Flex - 1613 Flex
250HP +/-186 KW +

Agricultural Tractor

1814 Flex - 2016 Flex
350HP +/-260 KW +

BLADE CONFIGURATIONS

8" (203mm) Curved Grader Blade

Straight Flat Cutting Edge

Serrated Cutting Edge

Specifications are subject to change without notice.