

TH5-19

CONSTRUCTION TELEHANDLERS



Key Features

- ✓ full size operator station
- ✓ All-in-one F-N-R joystick for machine and boom control
- ✓ Universal Skid Steer Quick Attach
- ✓ high visibility orange seat belt to verify operator use
- ✓ dedicated lift point on Quick Attach system for lifting suspended loads

Key Specifications

- ✓ 5,500 lbs. (2495 kg) maximum lifting capacity
- ✓ 19' 1" (5.8 m) maximum lifting height
- ✓ Features minimum turn radius of 10' 10" to outside tires
- ✓ 74 hp (55.4 kW) Kubota diesel engine

SPECIFICATIONS

		IMPERIAL
Capacities	Max. capacity	5500 lb
	Max. lifting height	19 ft 1 in
	Max. outreach	11 ft 2 in
	Breakout force with bucket	3425.13 daN
Weight and dimensions	Length to face of forks	12 ft 9 in
	Overall width	5 ft 11 in
	Overall height	6 ft 4 in
	Wheelbase	91 in
	Ground clearance	13 in
	Overall cab width	31 in
	Tilt-up angle	12 °
	Tilt-down angle	117 °
	External turning radius (over tyres)	10 ft 10 in
	Unladen weight (with forks)	10406 lb
	Tires type	Pneumatic
	Forks length / width / section	47 in x 5 in x 2 in
Performances	Lifting	8 s
	Lowering	5.40 s
	Extension	5.60 s
	Retraction	4.30 s
	Crowd	3.50 s
	Dump	3.60 s
Engine	Engine brand	Kubota
	Engine norm	Tier 4 final
	Engine model	V3307-CR-TE5B
	Number of cylinders / Capacity of cylinders	4 - 203 in³
	I.C. Engine power rating - Power	74 Hp / 55.40 kW
	Max. torque / Engine rotation	1033 ft/lbs @ 2600 rpm
	Drawbar pull	3229.40 daN
Transmission	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed	16 mph
	Max. travel speed (may vary according to applicable regulations)	16 mph
	Parking brake	Hydraulic spring release SAHR
	Service brake	Wet disc brakes
Hydraulics	Hydraulic pump type	Gear pump
	Hydraulic flow / Pressure	23 US gpm-3408 PSI
Tank capacities	Engine oil	3 US gal
	Hydraulic oil	30 US gal
	Fuel tank	17 US gal
Miscellaneous	Steering wheels (front / rear)	2 / 2
	Drive wheels (front / rear)	2 / 2
	Controls	Joystick



STANDARD FEATURES

- Four Wheel Drive
- Two-Speed Hydrostatic Drive System
- Back-Up Alarm
- Lockable Storage Box
- 12Volt Power Port
- Single Joystick F-N-R (JSM)
- Easy Manager
- Engine Block Heater
- Self-Leveling Forks

OPTIONAL FEATURES

- Suspension Seat
- Rearview Camera
- LED Work Lights
- Enclosed Cab with Heat and Defrost
- Air Conditioning
- Radio

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT