

# AL550

ARTICULATED LOADER

GEHL®



## KEY FEATURES

- 4-Post Open Canopy ROPS and FOPS Certified
- Proportional Auxiliary Hydraulics with Case Drain\* and Circuit Pressure Dump
- Inching Pedal
- Digital Display with Audible and Visual Indicators
- Differential Lock (*Hydraulically Activated Front and Rear*)
- Power-A-Tach® Attachment Mounting System (*4-Point, Skid Steer and EuroStyle*)
- Lift Arm with Z-Bar Kinematics Return to Dig and Mechanical Self-Level
- Lift Arm Float Detent
- 3-Speed\*
- Hydraglide™ Ride Control\*
- High-Flow Auxiliary Hydraulics\*

\*Optional features

# AL550 ARTICULATED LOADER



## SPECIFICATIONS

	IMPERIAL	METRIC	
<b>DIMENSIONS</b>	Height to Top of Cab / ROPS	91.06"	2313 mm
	Width over Tires*	58.23"	1479 mm
	Length with Bucket on Ground	186.46"	4736 mm
	Height to Hinge Pin Fully Raised	124.45"	3161 mm
	Maximum Dump Angle at Full Height	44.7°	
	Outer Turning Radius	126.18"	3205 mm
	Articulation Angle from Center	45°	
<b>CAPACITIES</b>	Static Tipping Load with Bucket Straight	4830 lbs	2190 kg
	Static Tipping Load with Bucket Full Turn	3734 lbs	1693 kg
	Static Tipping Load with Forks Straight	3410 lbs	1547 kg
	Static Tipping Load with Forks Full Turn	2655 lbs	1204 kg
	Bucket Breakout (kg)	9733 lbs	4425 kg
	Operating Weight with Bucket	7470 lbs	3388 kg
	<b>ENGINE</b>	Engine Manufacturer	Deutz
Model / Number of Cylinders		TD 2.2 L3 / 3	
Gross Power @ 2300 rpm		60 hp	44.7 kW
Displacement		0.48 gal	2.2 L
<b>HYDRAULICS</b>	Work Hydraulic System Flow	15.4 gpm	58.3 L/min
	Drive Hydraulic System Pressure	3045 psi	210 bar
	Drive Hydraulic Reservoir Capacity (L)	11.9 gal	45 L
<b>OTHER</b>	Travel Speeds	12.4 / 17.5 mph	20 / 28 km/hr
	Fuel Tank Capacity	21.8 gal	82.5 L
	Tires	<b>US</b> 33 x 15.5 - 16.5 <b>EU</b> 15.0 x 55 - 17	

\*Dependent on type of tires

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly.

GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



GEHL COMPACT EQUIPMENT

West Bend, WI 53095 U.S.A. | Tel: 262-334-9461 | Fax: 262-338-7517

## STANDARD FEATURES

- 4-Post Open Canopy ROPS and FOPS Certified
- Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- Hydrostatic 2-Speed Transmission
- Load Arm Float Detent
- Inching Pedal
- Electronic Hand Throttle
- Digital Display with Audible and Visual Indicators
- Adjustable Steering Column
- Cup Holder
- Differential Lock (Hydraulically Activated Front and Rear)
- Oscillating Front Frame
- Rubber Floor mat
- Power-A-Tach® Attachment Mounting System (EuroStyle, 4-Point & Skid Steer)
- Adjustable Arm Rest
- Adjustable Seat
- 12-Volt Socket in Arm Rest
- Lift Arm With Z-Bar Kinematics, Return to Dig & Mechanical Self-Level
- Multi-Function Joystick
- Lift / Tilt Electronic Lockout Switch
- Reverse and Brake Tail Lights
- Master Electrical Disconnect Switch
- Articulation Locking Bar (conforms to SAEJ276)
- Horn
- Side View Mirrors
- Front and Rear Worklights

## OPTIONAL FEATURES

- Cabin with Heat
- Cabin with Heat and Air Conditioning
- 3-Speed - 5 / 12 / 19 mph (8 / 20 / 30 km/hr)
- Adjustable Air Suspension Seat
- LED Work Lights
- Speed Control
- Back-up Alarm
- Hydraglide™ Ride Control
- Rear Auxiliary Hydraulics
- Additional Set of Front Auxiliary Hydraulics
- High-Flow Auxiliary Hydraulics
- Radio (Bluetooth Hands-Free)
- Rotating Beacon
- Strobe Light
- Lockable Tool Box
- Front and Rear 12-Volt Electric Auxiliary
- License Plate Holder
- Rear Hitch - Clevis or Receiver
- 3 inch (75 mm) Seatbelt