

V360

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ NEW Color Display with Keyless Start + Security Code
- ✓ NOW STANDARD Pilot Joystick Controls
- ✓ NEW Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Variable Hydraulics with Drain Case
- ✓ NEW LED Work, LED Rear Lights + Egress Lighting

IMPERIAL

		IMPERIAL
CAPACITIES	Operating Capacity At 50% Tipping Load	3600 lb
	Rated Operating Capacity with Optional Counterweight	3800 lb
	Operating Weight	10320 lb
	Tipping capacity	7200 lb
WEIGHT AND DIMENSIONS	Wheelbase	52 in
	Overall Operating Height - Fully Raised	175 in
	Height to Hinge Pin - Fully Raised	136 in
	Overall Height to top of ROPS	84 in
	Dump angle at full height	41 °
	Dump height	105 in
	Overall length with bucket	156 in
	Dump reach - Full height	31 in
	Rollback at ground	29 °
	Rollback Angle at Full Height	94 °
	Seat to ground height	43 in
	Overall width less bucket	75 in
	Bucket Width	84 in
	Ground clearance	10 in
	Overall length - Less Bucket	125 in
Clearance Radius - Front with Bucket	93 in	
PERFORMANCES	Travel speed (unladen)	7 mph
	Travel Speed with Two-Speed Option - Maximum	12 mph
WHEELS	Standard tires	14.00 x 17.5 HD
ENGINE	Engine brand	Deutz
	Engine model	TCD3.6
	Max. torque / Engine rotation	339 ft/lbs / 1600 rpm
	Power source	Battery
	Engine power (Hp / kW)	114 Hp / 85 kW
	Starter	4 kW
HYDRAULICS	Standard flow - Auxiliary hydraulics	25 US gpm
	Auxiliary Hydraulic Pressure	3450 PSI
	High-Flow Auxiliary Hydraulics - Option	40 US gpm
	High-Flow Auxiliary Hydraulics Pressure - Option	3450 PSI
TANK CAPACITIES	Fuel	28 US gal
	Hydraulic tank capacity	7 US gal



GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT