

VT360

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ NEW Color Display with Keyless Start + Security Code
- ✓ NOW STANDARD Pilot Joystick Controls
- ✓ NEW Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Variable Hydraulics with Drain Case
- ✓ NEW LED Work, LED Rear Lights + Egress Lighting

IMPERIAL

		IMPERIAL
CAPACITIES	Operating Weight	12161 lb
	Unladen weight	11094 lb
	Operating Capacity at 35% Tipping Load	3600 lb
	Operating Capacity At 50% Tipping Load	5143 lb
	Operating capacity at 35% tipping load with counterweight	3750 lb
	Tipping capacity	10287 lb
WEIGHT AND DIMENSIONS	Wheelbase	67 in
	Overall Operating Height - Fully Raised	174 in
	Height to Hinge Pin - Fully Raised	136 in
	Reach - Fully Raised	37 in
	Dump angle at full height	41 °
	Dump Height - Fully Raised	105 in
	Overall Height to top of ROPS	84 in
	Overall length with bucket	156 in
	Overall Length without Bucket	125 in
	Specified Height	101 in
	Reach at Specified Height	39 in
	Ground clearance	9 in
	Crawler base	67 in
	Overall width less bucket	80 in
Bucket Width	84 in	
Clearance Radius - Front with Bucket	96 in	
PERFORMANCES	Ground Speed - Single Speed	6 mph
	Ground Speed - Two Speed	9 mph
ENGINE	Engine brand	Deutz
	Engine model	TCD3.6
	Engine power (Hp)	114 Hp
	Engine power (kW)	85 kW
HYDRAULICS	Standard flow - Auxiliary hydraulics	25 US gpm
	High-Flow Auxiliary Hydraulics - Option	40 US gpm
TANK CAPACITIES	Hydraulic tank capacity	7 US gal
	Fuel	38 US gal



GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT